


REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DATE
A	CREATION	GI	GI	1/23/2011



Colour	Standard is Black. Optional White
HF Marine Band	2-30 MHz
Length	6.7 metres (22 ft)
Pattern	Omnidirectional
Polarisation	Vertical
Base Diameter	32mm (1.25 in)
Frequency Range	Pre-tuned to frequency or frequencies required, or unloaded 2-30 MHz with suitable ATU
Wind Loading	7.7 kg at 100 km/h (16.9 lbs at 60 mph) 13.0 kg at 130 km/h (28.6 lbs at 81 mph)
Power Capability	1 kW PEP for normal loaded or unloaded top sections; 500 W PEP for trapped top sections; higher power to order
Mounting	Two 100mm (4 in) nylon clamp type insulators, 50mm (2 in) diameter, threaded to take ½ inch Whitworth bolt (not supplied); insulator spacing not less than 0.9 m (3 ft)
Connection	Silicone insulated flexible cable tail 2.5 m long (8 ft) 56/0.3 tinned copper; length should not exceed that provided for correct operation on the higher frequencies
Packed Weight	7.25 kg (15.95 lbs) with mountings

UNLESS OTHERWISE SPECIFIED DIMENSIONS : mm ANGLES : d.		NEARSON INC.	
CUSTOMER N°	TITLE : Marine antenna for vessels		
FILE N°			
	SIZE A4	NMO-01-0019	REV A
	SCALE : N.D.		Prod. Doc.