				· · · · ·		
		REV	MODIFICATIONS			DATE
		Α	CREATION	GI	GI	7/13/2011
	Colour 27 MHz Marine Band Length Base Diameter Pattern Polarisation Frequency Range Bandwidth Impedance Wind Loading Power Capability Mountings Connection Packed Weight		Standard is Black. Opti 27.5-28 MHz 2.7 metres (8.9 ft) 35mm (1.4 in) Low angle, omnidirection Vertical 27.5-28 MHz; other free 0.6 MHz (at 2:1 SWR) 50Ω (nominal) 1.5 kg at 100 km/h (3.3 2.5 kg at 130 km/h (5.5 25 watts CW, 50w PEP Normally supplied with mount; also available w swingdown mount or 12 permanent mounting 3.65m (12 ft) 6mm (0.2 with PL259 UHF type of 3 kg (6.6 lbs)	onal White. onal quencies to lbs at 60 m lbs at 81 m polycarbona ith 316 stair 2mm metric 5 in) coaxia	order ph) ph) ate swir nless st bolt for	ngdown eel
	UNLESS OTHERWISE SPECIFIED DIMENSIONS : mm ANGLES : d. CUSTOMER N* FILE N*		<b>NEARSC</b> For communication Marine and Citizer	ns in the		
rawing is the property of Nearson Inc. and is issued on the condition that it is not conied.		SIZE A4 scale : n.d				REV A Prod. Doc. SHEET 1 of 1

This drawing is the property of Nearson Inc, and is issued on the condition that it is not copied or disclosed to any third party without prior written consent from Nearson Inc.