

M39029 PIN(插針)和Socket(插座)接觸點

工作溫度： -65° C (-85° F) 至+ 200° C (+ 392° F)

主體：銅合金，硬鍍金

耐久性： 500次插拔以上

M39029規範涵蓋了可拆卸壓接型、焊接型使用的接觸點。這些接觸提供優良的可靠性信號在高度苛刻的環境傳遞，已經成為廣泛的軍事、商業和工業系統的連接器的附件。M39029的接觸點有各種尺寸、材料可供選擇使用。

可供標準和其他的PIN(插針) (MIL-DTL-38999、MIL-DTL-24308、MIL-DTL-38999系列I，II，III，IV、MIL-DTL-83733) 和Socket (插座) 供連接器使用。

M39029產品規格

Slant	Socket/Pin	Size	Description
M39029/1	Pin	-	Crimp removable
M39029/4	Pin	-	Crimp removable
M39029/5	Socket	-	Crimp removable
M39029/9	Pin	-	Crimp removable, thermocouple
M39029/10	Socket	-	Crimp removable, thermocouple
M39029/11	Pin	-	Crimp removable
M39029/12	Socket	-	Crimp removable
M39029/16	Socket	-	Crimp removable
M39029/17	Socket	-	Crimp removable
M39029/18	Pin	-	Crimp removable
M39029/22	Socket	-	Crimp removable
M39029/25	Pin	-	Crimp removable, shielded
M39029/26	Socket	-	Crimp removable, shielded
M39029/27	Socket	12	Crimp removable, shielded
M39029/28	Pin	12	Crimp removable, shielded
M39029/29	Pin	-	Crimp removable
M39029/30	Socket	-	Crimp removable
M39029/31	Pin	-	Crimp removable
M39029/32	Socket	-	Crimp removable
M39029/33	Pin	-	Crimp removable
M39029/34	Pin	-	Crimp removable
M39029/35	Socket	-	Crimp removable
M39029/36	Pin	-	Crimp removable
M39029/37	Socket	-	Crimp removable



佳昭企業有限公司
NEARSON ENTERPRISE CORP.

• TEL:886-2-2957-9823 • FAX:886-2-2957-9712
• <http://www.nearson.com.tw>

M39029/44	Pin	–	Crimp removable
M39029/45	Socket	–	Crimp removable
M39029/46	Socket	–	Crimp removable
M39029/47	Pin	–	Crimp removable
M39029/48	Pin	–	Crimp removable
M39029/49	Socket	–	Crimp removable
M39029/50	Pin	–	Crimp removable, shielded
M39029/51	Socket	–	Crimp removable, shielded
M39029/55	Socket	–	Crimp removable, shielded
M39029/56	Socket	–	Crimp removable
M39029/57	Socket	–	Crimp removable
M39029/58	Pin	–	Crimp removable
M39029/59	Socket	8	Crimp removable, shielded
M39029/60	Pin	8	Crimp removable, shielded
M39029/63	Socket	–	Crimp removable
M39029/64	Pin	–	Crimp removable
M39029/69	Socket	–	Crimp removable
M39029/70	Pin	–	Crimp removable
M39029/71	Pin	–	Removable, solderless wrappost termination
M39029/72	Socket	–	Removable, solderless wrappost termination
M39029/73	Socket	12	Solder, removable, shielded
M39029/74	Pin	12	Solder, removable, shielded
M39029/75	Socket	12	Crimp removable, shielded
M39029/76	Pin	16	Crimp removable, shielded
M39029/77	Socket	16	Crimp removable, shielded
M39029/78	Socket	16	Crimp removable, shielded
M39029/79	Pin	–	Crimp removable, shielded
M39029/80	Socket	–	Crimp removable, shielded
M39029/83	Pin	–	Crimp removable
M39029/84	Socket	–	Crimp removable
M39029/85	Pin	–	Crimp removable, thermocouple
M39029/86	Socket	–	Crimp removable, thermocouple
M39029/87	Pin	–	Crimp removable, thermocouple
M39029/88	Socket	–	Crimp removable, thermocouple
M39029/89	Socket	–	Crimp removable, thermocouple
M39029/90	Pin	8	Concentric twinax
M39029/91	Socket	8	Concentric twinax, shielded
M39029/92	Socket	–	Crimp removable
M39029/93	Pin	–	Crimp removable



佳昭企業有限公司
NEARSON ENTERPRISE CORP.

• TEL:886-2-2957-9823 • FAX:886-2-2957-9712
• <http://www.nearson.com.tw>

M39029/94	Socket	–	Crimp removable
M39029/101	Socket	–	Crimp removable
M39029/102	Pin	12	Crimp removable, coaxial
M39029/103	Socket	12	Crimp removable, coaxial
M39029/106	Socket	–	Crimp removable
M39029/107	Pin	–	Crimp removable
M39029/112	–	–	Contact bushing, wire barrell
M39029/113	Pin	8	Concentric twinax
M39029/114	Socket	8	Concentric twinax



佳昭企業有限公司
NEARSON ENTERPRISE CORP.

• TEL:886-2-2957-9823 • FAX:886-2-2957-9712
 • <http://www.nearson.com.tw>