

Tin (Silver) Plated Copper Wire Shielding Braids (Tubular ; Flat)



Federal Specification QQ-B-575

Part Number	QQ-B-575 PART NUMBER	NOMINAL INSIDE DIAMETER	WIRE SIZE AWG	NUMBER OF WIRES	BRAID SIZE AWG	CIRCULAR MIL	FEET PER POUND	POUNDS PER 1000'
NSQ24136T	QQB575R36T031	.031"	36	24	22	600	500.	2.0
NSQ24236T	QQB575R36T062	.062"	36	48	19	1,200	250.	4.0
NSQ16234T	QQB575R34T062	.062"	34	32	19	1,351	233.	4.3
NSQ16132T	QQB575R32T062	.062"	32	16	20	1,011	303.	3.3
NSQ24336T	QQB575R36T078	.078"	36	72	18	1,800	167.	6.0
NSQ24436T	QQB575R36T109	.109"	36	96	16	2,400	122.	8.2
NSQ16434T	QQB575R34T109	.109"	34	64	16	2,544	114.	8.8
NSQ16232T	QQB575R32T109	.109"	32	32	17	2,023	152.	6.6
NSQ24536T	QQB575R36T125	.125"	36	120	15	3,000	97.	10.3
NSQ24334T	QQB575R34T125	.125"	34	72	16	2,862	109.	9.2
NSQ24232T	QQB575R32T125	.125"	32	48	15	3,034	99.	10.1
NSQ241036T	QQB575R36T156	.156"	36	240	12	6,000	47.8	20.9
NSQ24736T	QQB575R36T171	.171"	36	168	14	4,200	69.9	14.3
NSQ24534T	QQB575R34T171	.171"	34	120	13	4,770	64.1	15.6
NSQ24332T	QQB575R32T171	.171"	32	72	14	4,551	68.0	14.7
NSQ241336T	QQB575R36T203	.203"	36	312	11	7,800	35.7	28.0
NSQ24834T	QQB575R34T203	.203"	34	192	11	7,632	35.8	27.9
NSQ24532T	QQB575R32T203	.203"	32	120	11	7,585	40.7	24.6
NSQ241636T	QQB575R36T250	.250"	36	384	10	9,600	29.0	34.5
NSQ24530T	QQB575R30T281	.281"	30	120	9	12,000	23.8	42.0
NSQ48836T	QQB575R36T375	.375"	36	384	10	9,600	29.0	34.5
NSQ48534T	QQB575R34T375	.375"	34	240	10	9,540	30.6	32.7
NSQ48332T	QQB575R32T375	.375"	32	144	11	9,102	30.9	32.4
NSQ24730T	QQB575R30T375	.375"	30	168	8	16,800	17.5	57.0
NSQ241030T	QQB575R30T437	.437"	30	240	6	24,000	12.4	80.6
NSQ481136T	QQB575R36T500	.500"	36	528	9	13,200	21.0	47.7
NSQ48734T	QQB575R34T500	.500"	34	336	9	13,356	21.0	47.7
NSQ48432T	QQB575R32T500	.500"	32	192	9	12,136	25.0	40.0
NSQ241530T	QQB575R30T500	.500"	30	360	5	36,000	8.5	117.0
NSQ481030T	QQB575R30T562	.562"	30	480	3	48,000	6.6	151.0
NSQ481630T	QQB575R30T656	.656"	30	768	1	76,800	3.9	255.0
NSQ481836T	QQB575R36T781	.781"	36	864	7	21,600	13.6	73.5
NSQ481134T	QQB575R34T781	.781"	34	528	7	20,956	13.8	72.5
NSQ48732T	QQB575R32T781	.781"	32	336	7	21,239	13.8	72.7
NSQL48730T	QQB575R30T875	.875"	30	336	5	33,600	8.5	118.0
NSQL48830T	QQB575R30T1000	1.000"	30	384	4	38,400	7.4	135.0
NSQL48930T	QQB575R30T1125	1.125"	30	432	4	43,200	6.7	150.0
*NSQL481030T		1.250"	30	480	3	48,000	6.1	165.0
NSQL481130T	QQB575R30T1375	1.375"	30	528	3	52,800	5.6	180.0
NSQL481230T	QQB575R30T1500	1.500"	30	576	3	57,600	5.1	195.0
NSQL481430T	QQB575R30T2000	2.000"	30	672	2	67,200	4.4	225.0
*NSQL481630T		2.250"	30	768	1	76,800	3.9	255.0

(*)Manufactured to QQ-B-575 standards although these extra large sizes are not listed in the specifications.

QQ-B-575 : Federal Spec. R : Round. F : Flat. 36 : 36 AWG. S : Silver plated.
T : Tin plated. 500 : 0.500" inside Dia..

