		REV	MODIFICATIONS		CHECKED BY	DATE	
		A	CREATION	HE	HE	2/26/2013	
		А	OREAHOR		110	2/20/2013	
	Colour		Standard is Black				
	Frequency Range	Overall Length (approx) Radiator Diameter		30-88 MHz. 3.2m (10.5ft) 23mm (7/8 in) tapering to 12.7mm (1/2in)			
$\overline{\Lambda}$	Base Diameter		44mm (1.73 in)				
	Impedance		50Ω nominal				
	Power Capability		100w continuous	20 MU- 4			
	Gain (approx)		better than -10 dBi at	30 IVIHZ, -1.	o del at t	DU IVITIZ, +1.0	
	VSWR		dBi at 88 MHz <3.5:1				
	Pattern		Omnidirectional				
	Polarisation		Vertical				
	Wind Survival		Designed to withstan	d wind veloci	ities of 16	60 km/h (100	
			mph) no ice and 80 k				
			radial ice build up	、 ·	,		
	Connector		as required; please s	pecify			
	Mounting		Via ½ in Whit or 12m				
$\square$			stainless steel spring				
			swingdown mount (sp				
$\forall$	Weight		Antenna only 2kg (4.4	1 lbs); packe	d 3kg (6.	6 lbs)	
Н	UNLESS OTHERWISE SPECIFIED DIMENSIONS : mm ANGLES :	d.					
$\leftarrow$							
	CUSTOMER Nº	TITLE	<sup>:</sup> Broadband VHF	Marine N	Nobile		
	FILE N°	-	Antenna Systen				
			, antonnia Oyoton				
		SIZE				REV	
		A4	NMO-(	11_006	37	A Prod. Doc.	
				000-10	, ,		
This drawing is the property of and is issued on the condition that it is r		SCALE : N.				SHEET 1 of 1	

, and is issued on the condition that it is not copied or disclosed to any third party without prior written consent from